

PRODUCT DATA SHEET

OZ-720 MINERAL 15W-40

ORIZONE 15W-40 (7LTR) API CI-4 Mineral Engine Oil Formulation:
Premium quality mineral-based engine oil formulated with advanced additive technology.
With 100% virgin base oil.

Product Benefits:

- Enhanced protection for diesel engines in the most demanding
- Prolonged engine life
- Outstanding control of high temperature deposits
- Excellent soot control
- Reduced engine scuffing and bore polishing due to enhanced high temperature
- Improved low temperature sludge control in stop and-go service
- Extended quality reserve for long term wear and deposit control
- Reduced oil consumption

Complete engine protection against:

- Starting friction
- Engine deposits
- Heat stress
- API-SN
- ACEA A3/B4-08

Physical Characteristics

Total Base Number (ASTM D2896)	9.4 mg KOH
Viscosity at 100°C (ASTM D445)	14.9 cSt
NOACK Volatility (ASTM D5800)	10 mass % lost
High Temperature High Shear at 150°C (ASTM D4683)	4.2 mPa-s HTHS150

Safety

Should be stored under cover and where outside storage is unavoidable to avoid the possible ingress of water and damage. Products shouldn't be stored up to 60°C direct exposed to hot sun or freezing conditions. Use gloves and avoid direct contact with skin, wash immediately with soap and water if unavoidable.

This data sheet and the information it contains is believed to be accurate but it may vary from time to time. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data and information are provided always follow manufacturer's recommendations and specifications for viscosity grade and API service.

Orizone Prestige Sdn Bhd

45, Jalan Nautika B U20/B, Seksyen 20,
Pusat Komersil TSB, 40160 Shah Alam, Selangor, Malaysia.
EMEL : orizoneprestigesb@hotmail.com
WEBSITE : <https://orizonelube.com>



American
Petroleum
Institute

