

PRODUCT DATA SHEET

OZ-700 FULLY SYNTHETIC 5W-30

ORIZONE 5W-30 (7LTR) API CJ-4 Fully Synthetic Engine Oil Formulation:
Fully Synthetic 5W30, formulated with a synthetic base with high lubricating properties.
With 100% virgin base oil.

Product Benefits

- Improves fuel economy
- Safe for the environment
- Prolongs engine lifespan
- Offers better acceleration response
- Outstanding control of high temperature deposits

Suitable for use

- API CJ-4, CI-4 PLUS, CI-4, CH, CG-4 CF-4, SN
- Global DHD-1
- Mack EO-O Premium Plus/ Volvo VDS-4 Renault RLD-3
- MAN M 3575
- Cummins CES 20081
- MTU Oil Category 2.1
- Caterpillar ECF-2 & ECF-3
- JASO DH-2
- Detroit Diesel Power Guard Oil Specification 93K218
- Mercedes-Benz Approval 228.3 and 228.31
- ACEA E9-12. ACES E9-16

Physical Characteristics

Total Base Number (ASTM D2896)	10 mg KOH
Viscosity at 100°C (ASTM D445)	11.79 cSt
NOACK Volatility (ASTM D5800)	11 mass % lost
High Temperature High Shear at 150°C (ASTM D4683)	3.5 mPa-s HTHS150

Safety

Should be stored under cover and where outside storage is unavoidable to avoid the possible ingress of water and damage. Products shouldn't be stored up to 60°C direct exposed to hot sun or freezing conditions. Use gloves and avoid direct contact with skin, wash immediately with soap and water if unavoidable.

This data sheet and the information it contains is believed to be accurate but it may vary from time to time. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data and information are provided always follow manufacturer's recommendations and specifications for viscosity grade and API service.

Orizone Prestige Sdn Bhd

45, Jalan Nautika B U20/B, Seksyen 20,
Pusat Komersil TSB, 40160 Shah Alam, Selangor, Malaysia.
EMEL : orizoneprestigesb@hotmail.com
WEBSITE : <https://orizonelube.com>



American
Petroleum
Institute

